Ink & Stain Resistant — Ultrafabrics



We have all experienced the dreaded results of a bad spill. Our Ink & Stain solution helps alleviate cleaning stress by uniting repellency without sacrificing style. It is trusted across all markets, perfect for any environment you want to defend against pesky stains. From busy commercial environments to homes with pets and kids, our Ink & Stain resistance is universal in its utility.

Featured Collections ——

Reef Pro | Ultraleather Pro | Ultraleather Pro IFR*

- Superior durability – industry-leading 14+ weeks hydrolysis results
- Premium, 100% polycarbonate construction withstands harsh cleaners and disinfectants
- Bleach cleanable with 1:5 bleach/water solution
- Enhanced resistance to tough stains including ballpoint pen, betadine, blood, denim dye, mustard & ketchup, and red wine
- Select styles include antimicrobial protection
- SCS Indoor Advantage Gold Certified and REACH compliant

Not that you would, but you could.

*Only available in the UK.


Antimicrobial*


Ink & Stain Resistant

Ink & Stain Resistant

Application

Interior Upholstery

General Specifications

Composition:
100% Polycarbonate Polyurethane Surface
100% Reinforced Rayon Backing
containing TENCEL™ Modal fibers (Ultraleather Pro)
65% Polyester, 35% Rayon Backing (Reef Pro)
50% Modacrylic, 50% Rayon Backing (Ultraleather Pro IFR)

Weight:
Approx. 9.7 - 12.1 oz. Per Square Yard
Approx. 330 - 410 Grams Per Square Metre

Thickness:
Approx. 0.80 - 1.15 Millimetres

Width:
54 Inches / 137 Centimetres

Repeat:
None

Performance

Abrasion:
ASTM D4157 / 400,000 - 500,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 120,000 - 200,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:
14+ Weeks
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating:	ASTM D751
Tear Strength:	ASTM D2261
Breaking Strength:	ASTM D5034
Tensile Strength:	BS EN ISO 1421
Antimicrobial:	ASTM E2180*

Colorfastness

Light:	AATCC 16.3, 200 Hours, Grade 4
	ISO 105 B02, Grade 6
Crocking:	AATCC 8, Grade 4-5 Wet & Dry

Flammability Requirements

- ASTM E84 (Adhered) - Class A
- CA TB 117 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- IMO FTPC Part 8
- BS EN 1021 Parts 1 & 2**
- BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5)

Included Collections Resist:

- Ballpoint ink
- Blood
- Mustard and Ketchup
- Betadine
- Denim*
- Red Wine

* Removal of denim dye may vary depending on the period of time the stain sets in. While Pro offers excellent protection, full removal is not guaranteed.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.

*Only pertains to Ultraleather Pro & Ultraleather Pro IFR
**Only pertains to Ultraleather Pro & Ultraleather Pro IFR



TENCEL™ is a trademark of Lenzing AG

ultrafabricsinc.com

Ultrafabrics® and logo and Ultraleather® are registered trademarks of Ultrafabrics Inc. Made in Japan.

2/22

Uf Ultrafabrics®