Outdoor Living — **Ultrafabrics**



To brave the outdoors you'll need a solution that stands up to the elements. Our Outdoor Living materials repel water and withstand fading to provide lasting beauty. Engineered with an EPA-registered defense against mildew, Outdoor Living represents comfort and protection combined.

Featured Collections ——

Residential: Brisa Forecast | Brisa Frontier | Coast | Cora | Pumice | Summit

Marine:
Above Deck — Coast | Pumice
Below Deck — All other collections

Contract: Coast | Pumice


- Superior durability – industry-leading 14+ weeks hydrolysis results
- Premium, 100% polycarbonate construction withstands harsh cleaners and disinfectants
- Coast, Cora, Summit and Pumice features an EPA-registered antimicrobial agent that inhibits the growth of bacteria and other microbes.
- Enhanced UV colorfastness
- Stays cool to the touch

Live outside the box.


Acoustics†


Breathable Comfort


Antimicrobial


Outdoor Living

Outdoor Living

Application

Interior Upholstery, Exterior Upholstery

General Specifications

Composition:
100% Polycarbonate Polyurethane Surface
65% Polyester, 35% Rayon Backing

Weight:
Approx. 10.9 - 11.5 oz. Per Square Yard
Approx. 370 - 390 Grams Per Square Metre

Thickness:
Approx. 1.05 - 1.15 Millimetres

Width:
54 Inches / 137 Centimetres

Repeat:
8"V x 10.5"H / 203mm V x 267mm H (Brisa Frontier & Summit)
3.94"V x 3.66"H / 100mm V x 93mm H (Cora)

Performance

Abrasion:
ASTM D4157 / 200,000 - 400,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 100,000 - 200,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:
14+ Weeks
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating:	ASTM D751
Tear Strength:	ASTM D2261
Breaking Strength:	ASTM D5034
Tensile Strength:	BS EN ISO 1421
Cold Crack:	FTM 5874 / CFFA 6a
Air Permeability*:	ASTM D737
Antibacterial:**	AATCC 147
Antimicrobial:**	ASTM E2180
Antimildew:	ASTM G21
Sound Absorption*:	ASTM C423

Colorfastness

UV:	ASTM G154, 1000 Hours
Light:	AATCC 16.3, 200 Hours, Grade 4
	SAE J2527 1500 kj, Grade 4**
	ISO 105 B02, Grade 6-8
Crocking:	AATCC 8, Grade 4-5 Wet & Dry
Chlorinated Water:	AATCC 162, Class 4-5
Perspiration:	AATCC 15, Class 5
Sea (Salt) Water:	AATCC 106, Class 4-5

Flammability Requirements

- ASTM E84 (Adhered) - Class A
- CA TB 117 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- IMO FTPC Part 8
- BS EN 1021 Parts 1 & 2††
- BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5)

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.

*Only pertains to Brisa Forecast & Brisa Frontier
**Only pertains to Coast, Cora, Pumice & Summit
†Only in North America
††Only pertains to Coast

CERTIFIED INDOOR AIR QUALITY SCS GLOBAL SERVICES
INDOOR ADVANTAGE GOLD FURNITURE

ultrafabricsinc.com

Ultrafabrics® and logo, and Brisa® are registered trademarks of Ultrafabrics Inc. Made in Japan.

2/22

Uf Ultrafabrics®